

# MAGSTRIPE

## MINIWEDGE SWIPE READER



#### OPERATING ENVIRONMENT:

Temperature

Operating: 32°F to 131°F (0°C to 55°C) Storage: -22°F to 158°F (-30°C to 70°C)

Humidity

Operating: 10% to 90% noncondensing Storage: Up to 100% noncondensing

Altitude

Operating: 0-10,000 ft. (0-3,048m) Storage: 0-50,000 ft. (0-15,240m)

#### SPECIFICATIONS:

Power Input:

From PC: 5VDC; power supplied by keyboard interface

Message Format: Keyboard Scan Code

Card Speed:

3 to 50 ips (7,62 to 127 cm/sec)

MTBF:

Electronics: 125,000 hours Head: 1,000,000 passes

Current: 20mA max

**Dimensions:** 

Length: 3.94 in. (100,0mm) Width: 1.28 in. (32,5mm) Height: 1.23 in. (31,3mm)

Weight:

Reader only: 5.8 oz. (165gr) Reader w/ cable: 6.5 oz. (184gr)

Cable Length: 6 ft. (1,8m)

Connectors:

6-Pin Mini Din (PS/2) and 5-Pin Din (AT);

includes adapter cable

### FEATURES:

- Powered by the keyboard port no external power supply required
- Small & low cost
- Single, dual or three track capability
- Green/red status indicator
- Reads driver's licenses and bank cards
- Bi-directional read capability
- Single cable adapts to AT or PS/2 configurations
- User programmable
- Drivers for Windows 95, 98, NT

#### STANDARD CONFIGURATIONS:

Description	Pearl White	Black
Track 2:	21080205	21080206
Tracks 1 & 2:	21080203	21080204
Tracks 1, 2 & 3:	21080201	21080202