

POS X

POINT OF SALE
PERFECTED

XPC600 SERIES

FANLESS ALL-IN-ONE TOUCHPC

Designed to be seen and not heard, the XPC600 offers cutting edge performance and rock-solid stability. Grease, lint, and dirt are no longer an issue due to its fanless design. The XPC600's solid die-cut aluminum heatsink encompasses the entire backside of the unit, allowing for cooler operating temperatures at higher CPU speeds. Perfect for Restaurants or any location where noise is at a premium, the XPC600 is the system of choice in Fanless technology.



KEY FEATURES


- CPU: Intel 1.6GHz Celeron M ~ 1.73GHz Pentium M
- Memory: 512MB DDR II RAM upgradable to 1GB
- Optional integrated MSR and Customer Display
- Rugged spill resistant metal housing
- Bump-free 90-degree tilting base
- Silent fanless operation
- Additional VGA output
- 3 year warranty



ALL-IN-ONE TOUCHPC

XPC600 Series Specifications

PART NUMBER	XPC600, XPC600-H, XPC600-P	XPC600-H1, XPC600-P1	XPC600-P1P
MOTHERBOARD	M6 400 MHz FSB		M6 533 MHz FSB
CPU	1.6 GHz Celeron M		1.73 GHz Pentium M
Chip Set	VIA VN800		
System Memory	512MB DDR II 533MHz	1 GB DDR II 533 MHz	
Video	VN800 Integrated Graphics Max 64 MB		
Audio	VIA VT1613 AC'97 chip on-board		
PORTS			
USB	4 x USB2		
Serial/Com	4 x RS232 optional configurable powered 5V, 12V by Jumper D-Sub 9 Pin Male		
Parallel	Supports SPP/ECP/EPP mode D-sub 25-pins Female		
LAN	1 10/100M RJ45 Wake-From-LAN Support		
2nd VGA	1 x 15 pin D-Sub Female		
Cash Drawer	2x RJ12 Cash Drawer port 12v/24v		
Mouse	1 x PS/2		
Keyboard	1 x PS/2		
Audio Out	1 x 3.5mm Audio-Jack		
Mic	1 x 3.5mm Audio-Jack		
HARD DRIVE	1 x 2.5" 40 GB		
PHYSICAL			
Housing	Die Cut Aluminum Basket, ABS Bezel		
Weight with Base	19 lbs		
Dimensions with Base	15" (W) x 10.0" (D) x 13" (H)		
Dimensions without Base	15" (W) x 3.5" (D) x 12" (H)		
Tilt Angle	0° to 90°		
Optional Mounting	VESA 75 x 75 mm		
Housing Color	Black		
LCD Display	15" 1024 x 768 pixel, 16.7M colors 250 nit		
Touch Screen	5-Wire Resistive, 35+ million taps per location		
ELECTRICAL	200W		
ENVIROMENTAL			
Temperature	32° F to 114° F operating		
Humidity	10% - 95% non-condensing		
Shock Resistance	Operating shock 5g		
WARRANTY	3 Year Limited		
CERTIFICATIONS	FCC Class A, CE, RoHs		



ACCESSORIES

XM130U	3 Track MSR with USB interface
XM130K	3 Track MSR with KBW interface
XP2200S	Integrated Customer Display