

Multi-ISO HF RFID reader for Motorola MC70/75/75A Terminal

+ *Features and benefits:*

- ✓ Mounts on the base of the MC70/75/75A terminal
- ✓ Motorola terminal retains full laser bar code functionality and wireless LAN
- ✓ RFID reader is powered from the host terminal
- ✓ Multi ISO RFID reading and writing at 13.56 MHz
- ✓ High frequency (HF) industry standard ISO 15693 smart labels including Texas Instruments Tag-it™ and Philips ICODE™ II ISO15693 – 13.56 MHz
- ✓ Complete Mifare™ family of ISO14443 transponders
- ✓ Software development kit (SDK) available for development of custom applications
- ✓ Integrated SAM interface
- ✓ Customer installable assembly - easily removed from handheld but with the option of locking screws where a more permanent attachment is required.
- ✓ Compatible with existing Motorola single slot desktop docking/charging cradle. USB and MC70/75/75A charge connections are brought through to the base of the HF RFID reader to allow charging and ActiveSync over USB with the Reader attached.



PART NO.
1059-01-SO-MC75-RFID

- + The reader provides the Motorola™ MC70/75/75A with High Frequency (HF) RFID functionality. The HF RFID attaches as a snap-on to the Motorola terminal and houses both the RFID reader and the antenna. Power for the reader is obtained from the terminal. The HF RFID reader provides the ability to read and write to a wide variety of transponders at 13.56 MHz including ISO 15693, ICODE (I & II) and the complete Mifare family of ISO14443 (A&B). Flash upgradeability of the RFID reader firmware provides future proofing of the reader. The data output from the RFID reader may be simply incorporated into a Pocket PC application using the Software Development Kit (SDK).
- + The Reader is available as an Explorer kit which contains the reader, sample RFID tags, a Software Development Kit (which includes a demonstration application, the source code for that application and full reader documentation)
- + Applications include: e-Payment, e-Toll Road Pricing, Authentication, e-Ticketing for Events & Public Transport, Logistics & Supply Chain Management.

Performance Characteristics

RF Transmit Frequency	13.56MHz
Supported RFID Standards	ISO14443A, ISO14443B, ISO 15693, ISO 18000-3, ICODE
Supported Tag-ICs :	<ul style="list-style-type: none"> ✓ Tag-it HF-I ✓ Tag-it HF-I Light S ✓ Philips ICODE SL2 ✓ Infineon ISO15693 ✓ MIFARE® Standard ✓ MIFARE® 4k ✓ MIFARE® Pro ✓ MIFARE® Ultralight ✓ MIFARE® DESFIRE ✓ MIFARE® SmartMX ✓ SLE 55Rxx ✓ SRF55VxxP +S ✓ SLE 66CL160S ✓ SLE 66CLX320P ✓ SR176 ✓ SRIX4K ✓ LRI 12 ✓ LRI 64 ✓ LRI 512 ✓ EM4135 ✓ KSW Temp Sense ✓ Sharp S ✓ ASK GTML ✓ ASK GTML2ISO ✓ TOSMART P064 ✓ Jewel Tag (IRT0302B11 KSW) ✓ ISO14443A Tags ✓ ISO14443B Tags ✓ ISO15693 Tags

Reading distance	Up to 8cm (3") using ISO7810 size credit card format transponders.
RF Transmission Speed	Up to 848 kBit/s

SAM support

SAM clock	3.39MHz
SAM VCC	5V
SAM type	Form factor compatible with GSM SIM footprint

Current consumption

Current Consumption	< 150 mA during RFID read
	< 30mA in standby mode
	0mA in shutdown mode

User indication

Red, Green LEDs	Flash indicating activity (function may also be customised)
-----------------	---

Connection Interfaces

Physical interface	USB and power in to charge MC70/75/75A
Reader power supply	Powered from host terminal
ActiveSync	via USB

Physical Characteristics

Dimensions	90x82x32mm (3.54"x3.23"x1.26")
Weight	95g (3.35 oz)
Enclosure material	Polycarbonate
Colour	Grey
Material finish	Sparked surface
Mechanical attachment	Snap-on action with optional locking screws
Docking	Attachment maintains dockability with Motorola docking cradle for charging and ActiveSync

Environmental

Operating Temperature	-10°C to +50°C (14°F to 122°F)
Storage Temperature	-40°C to +60°C (-40°F to 140°F)
Humidity	Up to 90% Relative humidity Non Condensing
Drop specification	1.3m (4.26ft) to concrete, 6 drops per 6 sides over operating temperature; 1.5m (5ft) to concrete, 2 drops per 6 sides at ambient temperature 23°C (73°F)

Sealing	Internal components conformal coated
Electrostatic discharge	+/-15kV air discharge, +/-8kV direct discharge
Construction	RoHS compliant
Regulatory	
EMI/RFI	EN 300 330, EN 301 489, CE marked
	USA - FCC Part 15
Electrical Safety	Europe - EN60950-1
	USA - UL60950
Notes	
All PCBs are conformally coated	



+ About TSL

TSL designs and manufactures both standard and custom embedded, snap on and standalone peripherals for handheld computer terminals. Embedded technologies include:

- RFID - Low Frequency, High Frequency and UHF
- Bluetooth
- GPRS/GSM
- IrDA
- Contact Smartcard
- Fingerprint Biometrics
- 1D and 2D Barcode Scanning
- GPS
- 802.11 Wi-Fi
- Magnetic Card Readers
- OCR-B and ePassport

Utilizing class leading Industrial design, TSL develops products from concept through to high volume manufacture for Blue Chip companies around the world. Using the above technologies TSL develops innovative products in a timely and cost effective manner for a broad range of handheld devices.

Telephone: +44 (0)1509 238248
Fax: +44 (0)1509 220020

Postal Address: Technology Solutions (UK) Limited,
Suite C, Loughborough Technology Centre,
Epinal Way,
Loughborough,
Leicestershire,
LE11 3GE.
United Kingdom.

Email: enquiries@tsl.uk.com



Technology Solutions (UK) Limited reserves the right to change its products, specifications and services at any time without notice. Technology Solutions (UK) Limited provides customer assistance in various technical areas, but does not have full access to data concerning the uses and applications of any customers products. Therefore, Technology Solutions (UK) Limited assumes no responsibility for customer product design or for infringement of patents and/or the rights of third parties, which may result from assistance provided by Technology Solutions (UK) Limited.

Rev 1.6 – 12th May 2011